



POWER PRO 3GF-L (AT4LH) DIESEL GENERATOR



GENERATOR SPECIFICATIONS

Type	Self-exciting, 2-pole, field rotating type
Voltage regulation system	N/A
Phase	Single
Rated voltage (V)	220
Frequency (Hz)	50
AC Current (A)	11.8
Rated output (KVA)	2.6
DC output (V-A)	12V/8.3A
Rated power factor (cosØ)	1

ENGINE SPECIFICATIONS

Engine	Single-cylinder, vertical, air-cooled, direct-injection diesel
Displacement	296cc
Bore x Stroke (mm)	78 x 62
Rated horsepower	6 (4.5kw)
Cooling system	Forced air cooling by flywheel fan
Lubrication system	Pressure splash, duplex type lubrication
Oil	SAE40,
Oil capacity (lt)	1.1
Fuel	Diesel
Fuel tank capacity (lt)	15
Starting mode	Recoil start

NOTE: Specifications may vary according to the types, and are subject to change without notice.

Head Office
Cnr. Third Ave. & Klippen Rd.
Vosterskroon, Nigel
PO.Box 111, Nigel, 1490
Tel: 011 730 3400
Fax: 011 814 2345
E-mail: info@turfmaster.co.za
Web: www.turfmaster.co.za

Bellville
Proton Crescent
Stikland
Tel: 021 945
4106/7/8

Durban
Unit 21, The Terrace,
2 Goshawk Rd, New Germany
Tel: 031 705 3323
Fax: 031 705 3315

Port Elizabeth
20 – 6th Ave, Walmer
Tel: 041 581 8443/4/5
Fax: 041 581 8446