



BOWLSKING SCARIFIER



SPECIFICATIONS

Electric Motor:
Petrol Engine:
Cutting width:
Blade Thickness:
Grassbox:
Cutting blades:
Wheels:
Drive:
Frame:
Depth Adjustment:

MODEL 755

220 volt, single phase, 1,1kW, 1440rpm. Fitted with thermal overload cut-out switch.
 Power pro, Robin, Honda, Briggs & stratton
 Approximately 755mm
 1mm only
 Optional extra
 Hardened and tempered spring steel, mounted on shaft. Easily replaceable.
 Rubber with double sealed ball-bearings
 Single wedge-type 'v' belt
 Heavy duty, welded and bolted construction.
 Using independent fine hand-screw adjusters

MODEL 510

Approximately 510mm
 Optional, 1mm or 2mm

The perfect machine for prevention of thatch build up on greens. Not only can it remove all the dead material at the end of winter, but it can be used throughout the season to maintain a fast, true green with a surface that will allow the maximum penetration of all the expensive fertilizer and water that is applied to it. The depth of cut is very finely adjustable without the use of tools, using independent hand-screws on either side of the machine. For bowling green use, with the 755mm model you use a grassbox to collect the majority of the cuttings, thus leaving the green in playable condition if required. For use on golf greens, the 510mm model is fitted with a petrol engine and a front wheel carriage which is operated from the handlebar, to lift the cutter into a transport position. This model is also highly effective for scarifying matted grasses such as kikuyu and can be fitted with either 1 or 2mm thick blades in various spacings to suit many different jobs.

We reserve the right to change prices, specification and equipment without notice and without obligation in respect of machines already manufactured.