



POWER PRO 72cc MS CHAIN SAW



SPECIFICATIONS (Power unit)

Engine	Single cylinder two-stroke engine
Displacement	72cc
Maximum engine speed with Cutting attachment	9000rpm
Sound pressure level L_{peq} (According to ISO 7182 1)	102 dB(A)
Sound power level L_w (According to ISO 9207 1)	113 dB(A)
Vibration measurement a_{eq} (According to ISO 7505 1)	Left handle - 5.8m/s ² Right handle - 7.5m/s ²
1) Weighted equivalent level includes idling, full load and racing with the same duration of exposure.	
Ignition system type	Electronic magneto ignition (breakerless)
Carburetor	All position diaphragm carburetor with integral fuel pump
Air filter	Flat, two part wire mesh filter
Fuel tank capacity (ml)	680
Fuel mixture	Unleaded mixed 25:1 with 2-stroke oil
Oil tank capacity (ml)	360
Weight with bar and chain	6.8kg

SPECIFICATIONS (Cutting head)

Guide bar type	Oregon
Chain sprockets	7-tooth for 3/8" pitch
Guide bar size (in. (mm))	20" (508)
Saw chain type	Oregon
Saw chain pitch (in.)	3/8"
Saw chain gauge (in.)	0.063
Saw chain Lubrication	Fully automatic oil pump

NOTE: Specifications may vary according to the types, and are subject to change without notice.

Head Office
 Cnr. Third Ave. & Klippen Rd.
 Vosterskroon, Nigel
 PO.Box 111, Nigel, 1490
 Tel: 011 730 3400
 Fax: 011 814 2345
 E-mail: info@turfmaster.co.za
 Web: www.turfmaster.co.za

Bellville
 Proton Crescent Stikland
 Tel: 021 945 4106/7/8
 Fax: 021 945 2371

Durban
 Unit 21, The Terrace,
 2 Goshawk Rd, New Germany
 Tel: 031 705 3323
 Fax: 031 705 3315

Port Elizabeth
 20 – 6th Ave, Walmer
 Tel: 041 581 8443/4/5
 Fax: 041 581 8446